TABLE OF TRAIN SPEEDS				
Seconds per Mile	Miles per Hour	Seconds per Mile	Miles per Hour	
51	70.6	66	54.5	
<b>52</b>	69.2	67	53.7	
<b>53</b>	67.9	68	<b>52.9</b>	
54	66.7	69	52.2	
55	65.5	70	51.4	
<b>56</b>	64.3	75	48	
57	63.2	80	45	
58	62.1	85	42.4	
59	61	90	40	
60	60	100	36	
61	59	120	30	
62	58.1	144	25	
63	57.1	180	20	
64	56.3	240	15	
65	55.4	360	10	

# CHICAGO, MILWAUKEE, ST. PAUL AND PACIFIC RAILROAD CO.

BURLINGTON NORTHERN INC.

# JOINT TIME TABLE No. 5

Taking effect at 1:01 A. M. Central Standard Time

**Sunday, June 11, 1972** 

For the government and information of employes only

### TRACK OPERATED BY BURLINGTON NORTHERN INC. 2 ST. CROIX TOWER TO DIVISION ST.—WESTWARD FIRST CLASS Distance from St. Croix Tower 9 7 Office Hours **STATIONS** NRPC NRPC Passenger Passenger Daily Daily ST. CROIX TOWER Continuous 5.23PM 9.14 PM CURRY 5.0 No Office ST. PAUL PARK No Office 10.7 **NEWPORT** 11.9 Continuous RED ROCK 13.0 No Office DUNN 14.8 No Office OAKLAND 16.4 Continuous ST. PAUL YARD 17.2 Continuous DAYTONS BLUFF 17.7 Continuous HOFFMAN AVENUE 18.6 Continuous -0.6 DIVISION STREET 19.2 Continuous A 5.55 PM A 9.45 PM S. O. ERICKSON, Train Dispatchers, Newport. R.G.JOHNSON. R. H. SHOBER. C. J. BRYAN. F. W. WALTON, P. A. MADSEN, Asst. Vice President H. E. OTTERNESS, B. G. McDowell, Transportation Operations Chief Dispatcher, Superintendent Minneapolis, Minn. J. B. DALEY, T. P. GERIS. TRACK OPERATED BY CHICAGO, MILWAUKEE, ST. PAUL & PACIFIC RAILROAD CO.

### DIVISION ST. TO ST. CROIX TOWER—EASTWARD Capacity in Cars FIRST CLASS from St. 8 10 **STATIONS** Distance f NRPC NRPC Siding Passenger Passenger Other Daily Daily ST. CROIX TOWER 17.6 A 7.50 AM A11.40 AM CHEMOLITE 13.6 23 NEWPORT 7.3 79 RED ROCK 6.2 OAKLAND 2.8 Yard ST. PAUL YARD 2.0 Yard DAYTONS BLUFF 1.5 Yard HOFFMAN AVENUE DIVISION STREET 0.0 7.30 AM 11.20 AM

J. P. McMULLIN, G. A. JONASSON, P. J. ROONEY, R. SHIVE T rainmasters Twin City Terminal Officers have jurisdiction between Newport and Division St.

D. K. KRIDER, Traveling Engineer-Trainmaster E. P. SNEE, Ass't. Supt.
G. C. WILLIAMS, Asst. Trainmaster
J. J. TAYLOR, Asst. Trainmaster

W. F. PLATTENBERGER, Superintendent

LaCrosse Division Officers have jurisdiction between St. Croix Tower and Newport

H. M. HARRIS, Chief Dispatcher, La Crosse, Wis. C. Y. DEMPSEY, Traveling Engineer-Trainmaster

W. J. WESTMARK, Trainmaster, La Crosse, Wis.

F. A. BARTON, Superintendent, La Crosse, Wis.

## SPEED RESTRICTIONS

Location	Passenger Trains M. P. H.	Freight Trains M. P. H
Maximum Speed Eastward track	79 79 59	60 50 49
Trains making back-up movement on the west- ward track between St. Croix tower and St. Paul	20	20
wise specified	10	10
St. Paul Yard, and through crossovers between Eastward and Westward tracks at Oakland St. Croix Interlocking	25	25
Eastward track	40 30	$\begin{array}{c c} 25 \\ 25 \end{array}$
Through turnout from Eastward track to BN Eastward track	30	25
BN Westward track	30	25
Westward track	55	40
ward track Between MP 406.50 CMStP&P and Daytons	60	40
Bluff Westward track	75	
Oakland	75 45 30	25 25
Eastward track	75	
Between MP 396.62 CMStP&P and MP 395.60 CMStP&P Eastward track Between MP 395.60 CMStP&P and St. Croix	75	•••
Tower Eastward track	55	35

# SPECIAL INSTRUCTIONS

The two main tracks of the C.M.St.P.&P. and BN Railroads between The two main tracks of the C.M.St.F.&F. and BN Rainfoads Mewen St. Croix Tower and St. Paul are used as joint tracks. The C.M.St.P.&P. operate the eastward track and train orders will be issued over the signatures of the Superintendent at La Crosse. The BN operate the westward track and train orders will be issued over the signature of the Chief Dispatcher at Cicero.

These tracks are operated as double track. Unless otherwise provided by train order, trains must keep to the left. ABS is in use between St. Croix Tower and Division Street.

Rules 251, 252, 253 and 254 are in effect—EXCEPT CTC is in use on westward track between M.P. 403.43 and M.P. 406.34 and is controlled by the train dispatcher at Newport.

C.M.St.P.&P. Automatic Block and Interlocking signal aspects apply between Newport and St. Paul on westward track and between Newport and St. Croix Tower on eastward track.

Burlington Lines Automatic Block and Interlocking signal aspects as contained in the 1967 edition Consolidated Code of Operating Rules apply between St. Croix Tower and Newport on westward track and between St. Paul and Newport on eastward track.

In compliance with Rule D-91, the following will apply:

Where trains are to be moved against the current of traffic, following trains will not be permitted to enter the block until the preceding train is clear of the block.

Stop indication must be displayed immediately after rear of a train has passed the signal, and following trains will not be permitted to enter the block until it is clear of the preceding train.

Rules 91 and 91-A do not apply for movements against the current of traffic.

Protection against following trains on the same track is not required of trains moving against the current of traffic. This provision does not apply to any unit of equipment which does not actuate block or cab signals, or to a work extra.

Extra trains may be operated on eastward and westward tracks with current of traffic without train orders.

BN extra trains will not display classification signals.

Rule 83(B) does not apply at St. Croix Tower, Newport and Oakland if train order signal indicates proceed and only applies to eastward BN passenger trains at St. Paul. Such trains must obtain both a C.M.St.P.&P. and a BN clearance.

Interlockings are located at St. Croix Tower, Newport, Oakland, Hoffman Avenue and Division Street.

C.R.I.&P. trains will use joint tracks between Newport and St. Paul Train order signal at Newport does not govern C.R.I.&P. trains leaving C.M.St.P.&P.-BN joint tracks.

At Oakland, the westward train order signal does not govern trains terminating at Oakland or Daytons Bluff.

The Consolidated Code of Operating Rules, Edition of 1967, in addition to the following instructions will govern employes while operating on Minnesota Transfer Railway Co. and The St. Paul Union Depot Company trackage:

(a) All trackage of the Minnesota Transfer Railway Company is defined as a system of tracks within yard limits over which movements must be made at reduced speed and are not authorized by time-table, or train order, but subject to prescribed signals and rules or special instructions

The limits of The Saint Paul Union Depot Company property extend from connection with the BN tracks at Third Street and connection with the C.M.St.P.-BN tracks opposite depot round-house, on the east, to connection with the C.&N.W. Ry. and C.M.St.P.&P.R.R. tracks at Robert Street on the west

- (b) The time-table of The Saint Paul Union Depot Company is for information only Employes of railroads using the tracks of this Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company is for information only in the company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by current time-table of their respective Company will be governed by the comp panies only as to arriving and departing time of trains.
- (c) Where in the rules of the Consolidated Code reference is made to trains, such rules will also apply to yard movements and engines.
  - (d) Under Rule 10, the use of torpedoes is prohibited.
- (e) Under Rule 11, burning fusees must not be used except in case of emergency and then only when held in hand and must be extinguished before leaving.
- (f) There is no superiority of trains within the limits of The Saint Paul Union Depot Company property.
- (g) Within the limits of The Saint Paul Union Depot Company property trains and engines must move at restricted speed and must not exceed ten (10) miles per hour through crossovers, turnouts and puzzle

The entrance to and all movements on this property will be made only on authority of hand signals from switch tenders. No train or engine may foul any track or puzzle switch without authority of hand signals from switch tenders in control of such movements, except that short interior switching movements may be made through crossovers connecting shed tracks when authorized by train director.

Any lead or track may be used for the make-up of trains on authority of train director. The movement of trains should be given preference.

Switchtenders are equipped with yellow lightbulbs in their lanterns so as to distinguish their signals from other signals.

- (h) When indicated by the ringing of the bell, flashing of headlight, (h) When indicated by the ringing of the bell, flashing of headlight, hand or light signal that a train or engine is ready to move, the switchtender in charge of the shed track on which the movement is standing will handle as follows: at west end of station the switchtender will control the movement by hand or light signal; at the east end of station the switchtender will inform the train director, who will route the movement by instructions over the public address system. Switchtenders will be governed by these instructions, relaying such instructions by hand or light signal to the next switchtender in the direction of the movement, each must receive an acknowledgment before signalling the movement. Signals must not be acknowledged or acted upon unless the signal corresponds with instructions from the train director and is definitely understood.
- (i) When backing, the back-up air brake valve on passenger trains must be operated by the conductor, except in the movement of empty equipment, it may be operated by a competent trainman or yardman. When practicable, conductors must see that trainmen are stationed so hand or light signals may be used, in case of any emergency.

Mhen backing a train, the engine brake valve must be in running position; an application of the brakes must be made with back-up air brake valve before starting and it must be known that the brakes are in operative condition. Movement must not be started until the proper signal is given. A running test must be made with the back-up air brake valve before the train has moved 300 feet; if the running test is not made within 300 feet the engineer must stop the train and ascertain cause. The speed of train must not exceed eight (8) miles per hour and train must be under such control that it can be stopped short of train, or obstruction, and short of bumping post on stub tracks.

- (j) Headlights must be dimmed while on shed tracks.
- (k) Vestibule doors are to remain closed when trains are pulling or backing into the St. Paul Union Depot until the train comes to a complete stop.