

BURLINGTON NORTHERN INC.

OMAHA REGION

LINCOLN AND ALLIANCE DIVISIONS

Special Instructions No. 3

**IN EFFECT AT 12:01 A.M.
Central Standard Time
AND
MOUNTAIN STANDARD TIME**

Sunday, November 5, 1972

**Asst. Vice President
Transportation
R. G. JOHNSON**

**Superintendent
Lincoln Division
T. C. WHITACRE**

**Asst. Vice President
Operations
L. J. KING**

**Superintendent
Alliance Division
T. E. HUDSON**

ALL SUBDIVISIONS

1. Speed Restrictions—

	Maximum Speeds
Passenger trains	79 MPH.
Freight trains	60 MPH.
Unit coal trains	45 MPH.

The above speeds are subject to modification under speed restrictions indicated under each subdivision special instructions. All trains and engines through turnouts, crossovers and gantlets except as specified in special instructions or where fixed signals indicate otherwise 12 MPH.

Engines running light or with caboose only 50 MPH unless otherwise provided.

Unit trains and trains handling loaded 100-ton hopper cars, where speed of train cannot be maintained in excess of 21 MPH, immediately reduce speed to not exceed 13 MPH and do not exceed this speed until movement can again get up to exceed 21 MPH.

Equipment	Main Line	Branch Line
Ore cars	45 MPH.	20 MPH.
Scale test cars	35 MPH.	20 MPH.
Air dump cars (loaded)	35 MPH.	20 MPH.
Derricks	30 MPH.	15 MPH.
Cranes	30 MPH.	15 MPH.
Pile drivers	30 MPH.	15 MPH.
Clamshells and shovels.....	30 MPH.	15 MPH.
Jordan spreaders	30 MPH.	15 MPH.
Wedge plows and dozers (dead in tow)	35 MPH.	20 MPH.
Rotary plows	30 MPH.	20 MPH.

Maximum Speed Diesel Units Dead in Tow:

Switcher Units	50 MPH.
Road Switchers and other units.....	65 MPH.

Diesel engines, wrecking cranes and other types of heavy work equipment must not be operated on subdivisions on which they have not been previously operated until it is positively known that such movement can be made safely.

2. Movement of Diesel Units—

Diesel units not equipped with alignment control couplers when dead in tow in freight trains must be handled singly, not in groups and not less than 5 cars or more than 15 cars from the road engine.

When a locomotive consist of more than 3 units in service includes a diesel unit or units not equipped with alignment control couplers, only the three rear units will be allowed to work power when the train is to make a back-up movement. Other units must be isolated.

Diesel units not equipped with alignment control coupler:

All switcher units
 Road and Road Switcher Diesel units
 600- 995 inclusive
 1556-1623 inclusive
 4000-4197 inclusive
 6000-6255 inclusive
 9700-9800 inclusive
 9804-9807 inclusive
 9818-9830 inclusive
 9911-9995 inclusive
 All Fort Worth and Denver Railroad diesel units, also C&S units 150-842 inclusive.

3. At no time can more than seven high-horsepower units be coupled together as one consist (high-horsepower units include those with 3,000 horsepower or over).

On units with less than 3,000 horsepower, the number of units in any one consist will not exceed eight.

In the event Diesel units in excess of the above restrictions are to be handled dead in train, such units must be placed at least five cars, but no further than 15 cars, behind the lead units.

When road passenger units 9762 through 9794 are coupled in multiple with road freight or road switcher units, the road passenger units must be trailing to avoid danger of sliding wheels

on the freight or road switcher units due to excessive brake cylinder pressure. The speed restrictions for freight and road switcher units must be observed to avoid damage to traction motors.

4. Following equipment loaded or empty, must be handled on rear of trains unless otherwise provided:

Outfit cars
 Tie flats (GN X4800 to X4975, X4410)
 Scale test cars (next ahead of caboose)
 Wrecking derricks
 Pile drivers
 Loco cranes
 Rotary snow plows, dozers, wedge plows
 Jordan spreaders
 Air dump cars loaded or empty
 Log flats—NP 117002 to 117892 (BN 631661 through 631680)

Handling 80 foot or longer cars—

Trailing tonnage may cause lateral forces on 80 foot or longer cars that could result in derailing such cars where the combination of grade and curvature exceed certain limits. Equipment listed below must be handled in the rear 50 cars and as near the caboose as practicable where such limits exist, except that where helper is used on rear of the train a buffer of 10 or more cars of less than 80 foot ahead of the caboose must be maintained.

When remotely controlled units or helper units are in operation, such cars must be placed behind remotely controlled units and as near the caboose as practicable.

80 foot or longer flat cars empty or handling either a single loaded trailer, or empty trailers. 80 foot or longer flat cars handling container type units either loaded or empty. 80 foot or longer empty auto racks. Territory where such restrictions are in effect, are listed under each individual subdivision.

5. Remote Control Unit Operation—

When remote controlled units are used in trains, they must be placed in train approximately two-thirds back from head-end of train. Train tonnage will be limited by number of cars which may be handled over the various districts and tonnage ratings of the locomotive units used.

Repeater Relay Air Car Operation—

When repeater relay air car is to be operated in train, it must be placed approximately in the middle of the train.

6. When blowing snow or other conditions restrict visibility to the point that proper running inspection cannot be made, or when notified that a hot box detector is out of service, freight trains will reduce speed to the extent required, stopping if necessary, to make train inspection. Train crews will avail themselves of service stops to comply with the foregoing. Conductors will determine frequency of such inspection, dependent on visibility conditions, avoiding unnecessary delay to trains.

When a hot box detector is out of service, the requirements of Operating Rules or instructions will be suspended for defective equipment indicator associated with such hot box detector.

7. When derailment, collision, fire, or unforeseen occurrence takes place involving hazardous materials (such as explosives, flammable liquids, liquid petroleum gases, radioactive or fissionable material, poisons or chemicals). Conductor or other member of crew must check consist and/or waybills to determine if any such material is involved. If such material is involved crew members must stay out of the danger area and guard against people entering the area. Call Chief Dispatcher immediately and advise him of the materials and conditions. Be governed by his instructions.

8. At a railroad crossing at grade protected by signals, trains, engines or cars must not be left standing between opposing absolute signals unless coupled to other equipment that extends beyond one of the absolute signals.

When a train or engine is stopped by a stop indication of an automatic interlocking signal and no immediate conflicting train or engine movement is evident, in addition to complying with Consolidated Code Rule 613, employees must be governed by instructions posted in the release box.

LINCOLN DIVISION

(St. Joseph - Omaha)

FIRST SUBDIVISION

1. Speed Restrictions—	Maximum Speeds Permitted
Zone—Between	Freight
Napier and Pacific Junction	49 MPH.
Pacific Jct. and MP 491.00	50 MPH.
MP 60.40 and MP 64.00	20 MPH.
MP 64.00 and MP 65.25	30 MPH.
Amazonia and Savannah	25 MPH.
Engine or leading car over crossings MP 95.23 and MP 95.30 between Amazonia and Savannah	10 MPH.
Over Bridge 77.54	50 MPH.
At Pacific Jct., head end train 500 feet from railroad crossing until crossing occupied	15 MPH.
Curve, MP 487.88	50 MPH.
Curve, MP 490.60	30 MPH.
MP 491.00—East end of curve, Council Bluffs Yard ..	15 MPH.
N.&W. Crossing, Council Bluffs Yard, main track	15 MPH.
Head end of trains over 16th Ave. Council Bluffs Yard	202 MPH.
Through curve MP 492.24-MP 492.43 North track	15 MPH.
South track	15 MPH.
C.&N.W. Crossing, MP 492.86; I.C. Crossing, MP 492.99; C.R.I.&P. Crossing, MP 493.01	15 MPH.
Turnout end of two main tracks, Waterworks MP 67.12	50 MPH.
Eighth Subdivision main track turnout MP 97.40	
Napier	30 MPH.
Nodaway, Starks, Napier, Folsom & Island Park Siding turnouts	25 MPH.
MP 492.02, turnout, east end of two main tracks	15 MPH.
MP 492.80, turnout, west end of two main tracks	15 MPH.
Engines using Iowa Power track MP 489.01 must not exceed 15 MPH.	
Bridge Derrick 975501 and 250 ton wrecking derrick over Bridge 65.21 must not exceed 10 MPH.	
Derricks between Amazonia and Savannah 10 MPH.	
All trains; reduced speed between east end of U.P. Yard and 13th Street, through passenger yard, Omaha.	
Between Pacific Junction and BN Junction, Council Bluffs Yard, trains No. 1 and No. 2 with consist not exceeding 40 cars may observe maximum speed of 65 MPH except as follows: Operating at such speeds, trains will carry 110 pounds brake pipe pressure.	
Curve MP 490.60	55 MPH.
MP 491.00 east end of curve, Council Bluffs Yard	30 MPH.
N&W crossing, Council Bluffs yard, Main track	30 MPH.
Council Bluffs Yard, turnout, east end of two Main tracks	30 MPH.
Through curve MP 492.24 to MP 492.43 north track	20 MPH.
South track	25 MPH.
CNW crossing, MP 492.86; IC crossing, MP 492.99; CRIP crossing, MP 493.01	20 MPH.
2. Bridge, Engine and Heavy Car Restrictions—	
Cars heavier than the following not permitted without authority of Superintendent:	
40 ft. or less in length	220,000 lbs.
Over 40 ft. long	263,000 lbs.
Between Amazonia and Savannah	220,000 lbs.
Bridge derrick 975501 and 250 ton working derrick must not be operated between Amazonia and Savannah.	
SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U83C engines must not operate on following tracks:	
Hamburg—North Elevator	
St. Joseph—Trains and engines handling wide and low cars loaded with airplane parts and similar lading, must not operate	

9. Burlington Northern Signal Aspects and Indications as contained in pamphlet Form 15307 dated July 1st, 1971 is in effect. All employees concerned must be familiar with and comply with the new signal rules.

Employees in train, engine and yard service must have received a copy of Form 15307 before occupying the main track in any train or engine movement.

Block and Interlocking Signal Aspects and Indications shown on pages 94 through 117 also on page 124 of the Consolidated Code do not apply on this region.

Special signal aspects as shown for Burlington Lines on pages 118, 119, 120 and 121 of the Consolidated Code of Operating Rules remain in effect.

10. Rules 200 and 83(B) and other rules pertaining to authority for, and signatures on, train orders and clearances are modified to permit train orders and clearances to be issued by authority and over signature of the Chief Dispatcher.

Train orders and clearances for the First through the Tenth Subdivisions of the Alliance Division and from Hastings to Kene-saw of the Fourth Subdivision of Lincoln Division will be issued by the authority and over the signature of the Chief Dispatcher at McCook.

Train orders and clearances for the Eleventh through the Eighteenth Subdivisions of the Alliance Division will be issued by the authority and over the signature of the Chief Dispatcher at Alliance.

Train orders and clearances for the Eighteenth, Nineteenth, Twentieth, Twenty-Seventh and Twenty-Eighth Subdivisions of Lincoln Division will be issued by the authority and over the signature of the Chief Dispatcher at McCook.

11. Roadway signs indicate maximum speed for passenger trains. A triangle type sign with reflex letter Z indicates zone territory where maximum speed is indicated by numerals thereon, and will govern until next zone sign is reached. Where speed restrictions are required on curves within a zone, a banjo type sign with reflex letter C and numerals thereon will indicate maximum speed for that particular curve, after which zone speed may be resumed. Unless otherwise specified by timetable, bulletin, or special instructions these signs will be located one mile from point where zone speed changes or from point of curve.

12. If radios are provided, a voice test of the radio in the control unit and caboose must be made to determine if the radio is working properly before a train leaves its starting point.

If the radio is working properly, it must be turned on during entire trip with volume adjusted so calls may be received. Defective radio equipment must be reported to the chief dispatcher at first point of communication. The conductor and engineer will be equally responsible to see that these instructions are complied with.

13. In CTC territory, before using any electrically locked switch, permission must be obtained from the Control operator. Rule 281 is amended accordingly.

14. Employees are prohibited from working, riding, or moving from one unit to another on outside walkways when train is in motion, except that in case of necessity, or when passing signals, this may be done but speed of train must not exceed 25 MPH.

Under severe storm or adverse weather conditions, train must be brought to a stop before working on or passing from one unit to another on outside walkway.

15. Consolidated Code Rule 103(E), as contained in the 1967 edition, does not apply on Burlington Northern. The following rule applies:

103(E) Cars must not be handled ahead of the engine between stations outside of yard limits except when necessary to take cars to or from a spur track, or in work train service, or when it is necessary for a train to make a back-up movement. Such movements must be for no greater distance than necessary, and air brakes on such cars must be cut in and operative.

16. Within yard limits in non-ABS territory, the main track must not be used as a storage track except in case of emergency. When it becomes necessary to leave cars on main track in such territory, they must be protected by train order. This does not modify the requirement to move at reduced speed as required in Rule 93.

through passenger depot tracks 1, 2 and 3 account will not clear high platforms.

Omaha—Freight trains and movements handling piggybacks must not use depot tracks 2 to 5 inclusive.

3. Train Register Exceptions—

Napier, between 6:15 P.M. and 3:15 A.M. daily trains will register by register ticket. Between 3:15 A.M. and 6:15 P.M. daily trains will not register unless instructed to do so.

Bigelow, train register in depot. Corning, train register at West Wye Switch, trains will register when instructed to do so.

Pacific Jct.—Extra trains enroute to or from Council Bluffs Yard or Omaha via Second Subdivision, Ottumwa Division not required to stop Pacific Jct. may register by ticket.

4. Clearance Provisions and Exceptions Rule 83(B)—

Napier. Rule 83(B) does not apply to Eastward trains off Eighth Subdivision.

Pacific Junction. Trains must receive clearance.

Omaha. Rule 83(B) does not apply to eastward freight trains terminating at Council Bluffs Yard.

5. Track between Amazonia and Savannah is considered industrial track, Rule 105 applies. Lineup received for 1st Subdivision will cover.

6. At Hamburg—

Westward trains use siding East of depot; eastward trains use siding West of depot, unless otherwise provided.

Stop and protect switching movement over E Street.

7. At Pacific Jct.—The time of trains, via Bartlett, applies at the southeast wye track switch. Normal position of southeast wye track switch is for the wye.

8. At Council Bluffs Yard—Switching movements within the interlocking limits at CMStP&P-CRI&P-crossings MP 491.75, Council Bluffs Yard, may be made on permission from the control operator. Engine must follow each of the last six cars switched out of the interlocking limits. When stop signal governing movement over the crossing on BN main track fails to clear, Rules 606 and 269 must be complied with. Interlocking rules in effect for movements over crossing on BN yard lead.

When stop signal fails to clear for main track movement over N&W Crossing, MP 491.31; C&NW Crossing, MP 492.70; IC Crossing, MP 492.99; or CRI&P Crossing, MP 493.01, CTC Rules must be complied with and, in addition, movement over crossing must be made under protection.

N&W Crossing over freight track all movements must stop and be governed by signal indication.

9. At Omaha—Union Pacific Crossing between Junction with Union Pacific and Sixth Street, is protected by electrically locked gate, normally lined and locked for BN train movements.

10. Manual Interlockings not indicated at station between St. Joseph and Waterworks:

St. Joseph Term. Ry MP 61.51

Mo. Pac Crossing MP 61.90

U.T. Crossing MP 64.01

LINCOLN DIVISION

(Pacific Jct. - Carling)

SECOND SUBDIVISION

1. Speed Restrictions—

Maximum Speed Permitted

Zone—Between	Passenger	Freight
Pacific Junction to MP 0.95.....	40 MPH.	25 MPH.
Pacific Junction 500 feet from R.R. Crossing	15 MPH.	15 MPH.
MP 0.95 to MP 3.50.....	65 MPH.	40 MPH.
MP 3.50 to MP 5.00.....	40 MPH.	30 MPH.

Missouri River Bridge 3.80 and curve at west end of bridge.....	20 MPH.	20 MPH.
MP 5.00 to MP 8.79.....	55 MPH.	40 MPH.
MP 0.00 to MP 14.75 (Omaha Line).....	65 MPH.	50 MPH.
Curve MP 1.30.....	50 MPH.	40 MPH.
MP 14.75 to MP 15.99.....	50 MPH.	40 MPH.
MP 15.99 to MP 16.50.....	20 MPH.	20 MPH.
MP 16.50 to MP 17.22.....	10 MPH.	10 MPH.
MP 17.22 to MP 17.89.....	20 MPH.	20 MPH.
MP 17.89 to MP 21.50.....	50 MPH.	40 MPH.
Curve MP 19.12.....	20 MPH.	20 MPH.
MP 21.50 to MP 28.20.....	55 MPH.	50 MPH.
MP 28.20 to MP 41.90.....	60 MPH.	50 MPH.
MP 41.90 to MP 46.89 (MP 35.00 Louisville Line).....	75 MPH.	50 MPH.
Curve MP 46.10.....	55 MPH.	50 MPH.
MP 35.00 to MP 35.75.....	50 MPH.	40 MPH.
MP 57.00 to MP 58.87.....		50 MPH.
MP 58.87 to MP 59.35 via passenger line	25 MPH.	20 MPH.
MP 58.87 to MP 59.98 via freight line..	25 MPH.	25 MPH.
Between Baird Tower and Hall Tower via passenger tracks, Lincoln.....	25 MPH.	20 MPH.
Plattsburgh—Through turnout in south track MP 4.99.....	30 MPH.	30 MPH.
Oreapolis—Through turnouts	30 MPH.	30 MPH.
Gibson—Through turnout south track MP 14.96	30 MPH.	30 MPH.
Ashland—East crossovers MP 35.15 between south track and Omaha line.....	40 MPH.	40 MPH.
Between North track and Louisville line	30 MPH.	30 MPH.
MP 36.39 turnout west end No. 1 track..	30 MPH.	30 MPH.
MP 36.40 through crossover between main tracks	30 MPH.	30 MPH.
MP 41.10 through crossovers between main tracks	30 MPH.	30 MPH.
Greenwood—Turnout in north track at MP 42.66	40 MPH.	40 MPH.
Engine of freight train must not exceed MP 44.39 and MP 47.59.	55 MPH.	passing signals
Waverly—Turnout in north track at MP 47.56	40 MPH.	40 MPH.
Trains must not exceed 25 MPH. through turnouts of controlled sidings, except 15 MPH. through turnouts of controlled siding Omaha.		
Trains must not exceed speeds designated through the following dual control switch turnouts:		
Oreapolis wye	15 MPH.	
Pappio	30 MPH.	
Gibson, east yard switch MP 13.40.....	30 MPH.	
So. Omaha MP 19.78.....	15 MPH.	
Bellevue—SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C, and U33C engines must not exceed 20 MPH. on siding.		

2. Bridge, Engine and Heavy Car Restrictions—

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length.....	220,000 lbs.
40 ft. to 52.5 in length.....	263,000 lbs.
52.5 ft. or longer.....	315,000 lbs.

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

Plattsburgh	Lead to BREX yard
	Water Works
Ashland	Team track
	West Elevator track
Havelock	
South side of Main tracks	
East End	Storage track
	North paint line track
	All Shop tracks proper

South side of Main tracks
West End Roundhouse tracks
Shop lead
All Shop tracks proper

North side of Main tracks
West End Material yard lead cannot be used
beyond switch to No. 10 track
All material yard tracks

Plattsmouth. When picking up or setting cars on Water Works track, trains must hold onto enough cars to keep engine clear of turnout.

Omaha. Bridge derrick 975501 may operate on track 6 only and must keep off all other tracks adjacent to station canopies.

Trains handling piggy backs and freight trains must not use depot tracks 2 to 5 inclusive.

3. Train Register Exceptions—

Pacific Jct.—

First class trains will register by register ticket. Extra trains enroute to or from Ottumwa Division Second Subdivision not required to stop Pacific Jct. may register by ticket.

Omaha. Trains in through movement will not register.

4. Clearance Provisions and Exceptions Rule 83(B)—

Omaha. First class trains, trains turning and trains for which crews report for duty at Omaha must receive Clearance.

5. Between Pacific Jct. and Plattsmouth—

Between MP 3.5 and MP 4.5, when starting a freight train, minimum throttle position will be maintained to keep the speed slow and uniform until engine passes MP 3.5 eastbound and MP 4.5 westbound.

6. At Omaha—

Union Pacific Crossing between Junction with Union Pacific and Sixth Street, is protected by electrically locked gate, normally lined and locked for BN train movements.

Interlocking at Fifth and Howard Streets is automatic. Approach clearing sections are 500 feet in length and when occupied will cause signal to display a proceed aspect if no conflicting movements are being made. If movement approaching a clear signal aspect is delayed, signal may display a stop aspect after expiration of pre-determined time. Electrically locked derails on auxiliary tracks may be removed when movement has occupied short track circuit in advance of derail after switch padlock has been removed and indicator light displays. Derails must be restored and locked immediately after movement has cleared the derail. Push buttons on signals clear signal to make reverse movement or a forward movement after making reverse movement.

7. At South Omaha—

When westward trains enter South Omaha Yard by signal indication through dual controlled switch at MP 19.78, such indication will convey control operator's permission to enter controlled siding through spring switch at MP 20.29. Trains stopped or delayed in making this movement must receive permission from control operator before entering or fouling controlled siding. If conditions require, westward train will be stopped and notified by control operator before entering yard at MP 19.78.

8. At Lincoln—

Interlocking at Mo. Pac. Crossing MP 58.87 is manually controlled. Eastward signals are part of Centralized Traffic Control system. Westward signals are interlocked and are part of Baird Interlocking.

Centralized Traffic Control in effect on both freight tracks between Baird Interlocking limits and Hall Interlocking limits.

9. Automatic Interlocking not indicated at station:

C&NW Crossing 2.7 miles west of Havelock

10. Manual Interlocking not indicated at station:

Mo. Pac. Crossing 4.2 miles west of Havelock

LINCOLN DIVISION

(Oreapolis - Ashland)

THIRD SUBDIVISION

- Speed Restrictions**

Zone—Between	Maximum Speeds Permitted
	Freight
Maximum Speed	50 MPH.
Curves between MP 10.95 and MP 11.60.....	45 MPH.

Oreapolis:
Turnout at end of two main tracks..... 30 MPH.
West Wye switch and West leg of Wye..... 15 MPH.
Ashland, through crossover from Louisville line to north track 30 MPH.
Turnouts of controlled sidings..... 25 MPH.
Between Oreapolis and Ashland, Bridge Derrick 975501 and 250 ton wrecking derrick may operate 25 MPH.
- Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
40 ft. or less in length.....220,000 lbs.
40 ft. to 52.5 ft. in length.....263,000 lbs.
52.5 ft. or longer.....315,000 lbs.
- Train Register Exceptions—None.**
- Clearance Provisions and Exceptions Rule 83(B)—**
Oreapolis. Rule 83(B) does not apply.
Ashland. Rule 83(B) does not apply except westward trains, from Third Subdivision enroute to Tenth Subdivision must receive Clearance.
- Oreapolis—Mo. Pac. railroad crossing over west leg of wye protected by automatic interlocking signals.

LINCOLN DIVISION

(Lincoln - Kenesaw)

FOURTH SUBDIVISION

- Speed Restrictions—**

Zone—Between	Maximum Speeds Permitted	
	Passenger	Freight
Baird Tower and Hall Tower, via passenger tracks, Lincoln.....	25 MPH.	20 MPH.
Lincoln to MP 60.50.....	30 MPH.	20 MPH.
MP 60.50 to MP 66.70.....		50 MPH.
MP 66.70 to MP 70.50.....	60 MPH.	50 MPH.
Cushman-Cobb (Freight Line).....	35 MPH.	35 MPH.
MP 70.50 to MP 82.25.....	75 MPH.	50 MPH.
Curve MP 78.24.....	60 MPH.	50 MPH.
MP 79.00 to MP 80.40.....	30 MPH.	30 MPH.
MP 80.40 to MP 83.00.....		50 MPH.
Curve MP 127.52.....	70 MPH.	50 MPH.
MP 155.00 to MP 156.00.....		50 MPH.
MP 156.00 to MP 157.00.....	25 MPH.	25 MPH.
MP 157.00 to MP 158.00.....		30 MPH.
Cobb Turnout	25 MPH.	25 MPH.
Crossover MP 154.89, Brick Yard.....	30 MPH.	30 MPH.
Turnouts MP 155.82.....	30 MPH.	30 MPH.
Crossover MP 155.98.....	15 MPH.	15 MPH.
Crossover and turnouts MP 156.43.....	15 MPH.	15 MPH.
Turnout west end of No. 1 track MP 157.96	30 MPH.	30 MPH.
Turnout end of two main tracks Gaines..	40 MPH.	40 MPH.
SD-24, SD-45, U25C, U28C, U33C, SD-40 and U30C Engines on siding at Kenesaw		25 MPH.

Trains must not exceed 25 MPH. through turnouts of controlled sidings.
Westbound: Engines on freight trains must not exceed 55 MPH. passing signal at MP 130.1.

2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
40 ft. or less in length.....220,000 lbs.
40 ft. to 52.5 ft. in length.....263,000 lbs.
52.5 ft. or longer.....315,000 lbs.
SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:
BerksHouse track
HastingsCowten track Kearney Stub track
 Elevator track Byers Lumber Co. track
 Horn track Nash-Finch Co. track
 Standard Oil track All other industry tracks
JuniataHouse track
KenesawHouse track
 Elevator track
Crete—Engines must not go beyond hopper on oil track spur.
3. **Train Register Exceptions—**
Hastings Tower—Trains will register by ticket.
Gaines—Trains originating and terminating will register.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Crete—Rules 83(B) does not apply to eastward trains off Sixth Subdivision.
Hastings Tower—
Eastward trains must receive Clearance.
Westward trains originating at Hastings and Gaines must receive Clearance.
Hastings, Gaines and Kenesaw—Rule 83(B) does not apply.
5. **At Fairmont—**
Normal position Jct. switches as follows:
East end for Twenty-Fifth Subdivision.
West end for Fifth Subdivision.
6. **At Crete**—Switching movements over Main Street Crossing must be protected by a member of the crew in accordance with Rule 103 regardless of the position of the gates. On old Wymore main track cars must not be left less than 70 feet from either side of crossing. Eastward passenger trains making station stop should stop with head-end not less than 320 feet west of crossing.
7. **At Gaines**—Normal position of west switch off No. 1 track to No. 2 and No. 3 tracks is for No. 1 track.
8. Exeter CNW Crossing MP 105.08:
Paragraph (c) Rule 606 in effect for westbound movement only.

LINCOLN DIVISION

(Hebron - Fairmont)

FIFTH SUBDIVISION

1. **Speed Restrictions—** Maximum Speeds Permitted
Zone—Between Freight
Fairmont and Strang..... 35 MPH.
Strang and Hebron 30 MPH.
Westward trains over Highway Crossing
MP 0.94 10 MPH.
Belvidere. Engine or leading car at approach signal
and between absolute signals of interlocking..... 20 MPH.
Derricks between Strang and Hebron..... 10 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
40 ft. or less in length.....220,000 lbs.
Over 40 ft. long.....263,000 lbs.
Between Fairmont and Hebron, Bridge Derrick 975501 and 250 ton wrecking derrick must not operate.

3. **Train Register Exceptions—**
Strang—Trains will register when instructed to do so.
Train register at north switch at West wye.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Strang—Rule 83(B) does not apply.
5. **At Fairmont**—Normal position Jct. Switch west end Fairmont is for Fifth Subdivision.
6. **At Strang—**
Normal position of east and west wye switches of east wye on the Sixteenth Subdivision is for Sixteenth Subdivision.
Normal position of the South switch East wye is for the West leg of wye.
Normal position of east and west wye switches of west wye on the Sixteenth Subdivision is for the east and west legs of wye.
Normal position of the North switch West wye is for the West leg of wye.

LINCOLN DIVISION

(Crete - Wymore)

SIXTH SUBDIVISION

1. **Speed Restrictions—** Maximum Speed Permitted
Zone—Between Freight
Jct. switch at MP 0.77 and Beatrice..... 40 MPH.
Beatrice and Wymore 30 MPH.
Curve MP 1.00 20 MPH.
MP 17.16 and MP 17.42 DeWitt..... 15 MPH.
Over bridge 19.94 West of DeWitt..... 6 MPH.
MP 29.90 and 30.60 Beatrice..... 20 MPH.
Over Court and Sixth Street Beatrice..... 5 MPH.
Loaded tank cars 25 MPH.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C engines, single units only..... 30 MPH.
Between Crete and Wymore, Bridge Derrick 975501 and 250 ton wrecking derrick may operate 25 MPH. other derricks 30 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
40 ft. or less in length.....220,000 lbs.
Over 40 ft. long.....263,000 lbs.
SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:
ShestakElevator track
WilberSpur track
BeatriceCoal Track No. 3 track
 Kees track Creamery track
 No. 1 track Gas track
 No. 2 track Nemaha Main
Mile Post 31.84...Brick Yard Spur
3. **Train Register Exceptions—**
Crete—Westward trains will register by ticket when operator is on duty.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Crete—
Operator on duty 8:00 A.M. to 6:00 P.M. daily except Saturday and Sunday. Westward trains must receive Clearance when operator is on duty.
Beatrice—
Operator on duty 7:00 A.M. to 7:00 P.M. Tuesday through Friday.
Saturday: 11:00 A.M. to 7:00 P.M.
Monday: 7:00 A.M. to 3:00 P.M.
Trains must receive Clearance when operator is on duty.
5. Lights on Train Order Signals will not be displayed.
6. **Wymore**—All tracks within yard limits are yard tracks.
7. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Lincoln - Ravenna)

SEVENTH SUBDIVISION

1. **Speed Restrictions—**

Zone—Between	Maximum Speed Permitted	Freight
Lincoln and MP 1.10.....	20 MPH.	
MP 1.10 and Cushman.....	25 MPH.	
Engine or leading car over highway crossing "O" Street, MP 1.90 Westward.....	10 MPH.	
Engine or leading car over highway crossing "O" street MP 1.90 Eastward.....	15 MPH.	
Curves between MP 55.50 and MP 56.10.....	50 MPH.	
Aurora—Between MP 77.10 and MP 78.10.....	50 MPH.	
Grand Island—Between MP 95.70 and MP 96.50.....	30 MPH.	
Ravenna—		
Between MP 126.90 and MP 127.19.....	30 MPH.	
Between MP 127.19 and MP 127.74.....	20 MPH.	
Cushman—Turnout to passenger line.....	30 MPH.	
Seward—Through turnouts and spring switch both ends siding.....	25 MPH.	
Grand Island—Through turnout west of UP crossing.....	30 MPH.	
Ravenna—Through east turnout.....	30 MPH.	
MP 32.00 and MP 34.00.....	55 MPH.	
MP 53.00 and MP 55.00.....	55 MPH.	
Eastward freight trains—Engine passing signals at MP 125.99 and at MP 110.80.....	55 MPH.	
Between York and McCool Jct. and York and Benedict.....	20 MPH.	
Engine or leading car over Nobes Ave. between York and McCool Jct.....	10 MPH.	
2. **Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft or less in length.....	220,000 lbs.
40 ft. to 52.5 ft. in length.....	263,000 lbs.
52.5 ft. or longer.....	315,000 lbs.

Between York and McCool Jct. and York and Benedict.....210,000 lbs.

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

Grand Island.....	Oil track
Ravenna.....	City track
York to Benedict.	
York MP 135.00 to McCool Jct.	

Bridge derrick 975501 and 250 ton wrecking derricks must not operate York to McCool Jct. and York to Benedict.
3. **Train Register Exceptions—**

Cushman—Trains will register when instructed to do so.

Grand Island—
Register station for trains originating and terminating.
Trains in through movement will not register at Grand Island unless instructed to do so.
4. **Clearance Provisions and Exceptions Rule 83(B)—**

Eastward C&NW trains receive BN Clearance at C&NW Depot Seward.
5. Track between York and McCool Jct. and between York and Benedict is considered industrial track Rule 105 applies. Line-up issued for 7th subdivision will cover.
6. Columbus Jct. MP 1.00 to MP 4.76 west of Cushman one continuous yard.
7. **At Grand Island—**

When handling 85 foot cars or longer on 17 degree curve of Union Pacific freight house lead and interchange track, beginning 150 feet east of point of switch for freight house lead located in the direct interchange track and continuing westward

550 feet on to the freight house lead track, movement must not exceed 4 MPH. A member of crew must watch movement closely, prepared to give stop signal if any indication of failure to safely negotiate the curve. Particular attention must be given to lateral movement of coupler, as critical point of movement on curve develops when coupler approaches maximum lateral movement permitted by coupler opening.

Overhang at end of these cars is greater than on other cars and clearances must be watched closely when handling on curves in excess of 16 degrees.

LINCOLN DIVISION

(Napier - Carling)

EIGHTH SUBDIVISION

1. **Speed Restrictions—**

Zone—Between	Maximum Speed Permitted	Freight
Table Rock and Carling.....	49 MPH.	
Over Missouri River Bridge 8.93 at Rulo.....	10 MPH.	
MP 9.30 and MP 10.30 Rulo.....	35 MPH.	
MP 17.10 and MP 17.75 east of Falls City.....	35 MPH.	
MP 19.30 and MP 19.75 Falls City.....	25 MPH.	
MP 9.00 and MP 9.70 west of Elk Creek.....	35 MPH.	
MP 14.85 and MP 15.70 Tecumseh.....	40 MPH.	
MP 60.15 and MP 60.45.....	25 MPH.	
At the approach signal of interlocking Union Pacific crossing MP 61.39.....	25 MPH.	
Over Union Pacific Crossing MP 61.39.....	25 MPH.	
Trailing movement through spring switch MP 1.50 Napier.....	25 MPH.	
Engine of eastward freight trains must not exceed when passing signal at MP 38.90 east of Humboldt.	55 MPH.	
2. **Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

Rulo bridge MP 8.93.....	210,000 lbs.
40 ft. or less in length.....	220,000 lbs.
Over 40 ft. long.....	263,000 lbs.

Between Napier and Lincoln, Bridge Derrick 975501 and 250 ton wrecking derrick may operate. 250 ton derrick must have two lightly loaded cars between derrick and engine over bridge 8.93 Rulo.

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

Falls City.....	Roundhouse track
	James track
Tecumseh.....	No. 1 track
	No. 2 track
	No. 3 track
	Coal track
	City track
Adams.....	Spur track
Firth.....	Elevator track
	Stub track
Hickman.....	Stub track

Missouri River Bridge 8.93 Rulo—
SD-7 and SD-9 engines, may be operated over bridge single or when coupled with not more than two units of F, GP, U25B or U28B class engines.
SD-7 and SD-9 class engines, must not be operated over bridge when coupled with same class engines.
Five F, five GP, five U25B or five U28B units, or combination of five units consisting of F, GP, U25B or U28B class units may operate over bridge.
SD24, SD45, U25C, U28C, GP40, SD40, U30C and U33C may operate over bridge single unit only.
Additional engines must be spaced at least 10 cars from engine handling the train and no more units may be coupled together at such a location than are permitted at the head end of the train.

3. **Train Register Exceptions—**
Napier—Operator on duty 6:15 P.M. to 3:15 A.M., daily. Trains will register by ticket when operator is on duty. Trains will not register when operator is not on duty unless instructed to do so.
Table Rock—Trains will register when instructed to do so.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Napier—Westward trains must receive clearance when operator on duty.
5. **Falls City**—Westward movements on main track or siding meeting eastward movements will stop short at end of Overlap Sign located approximately 360 feet east of westward absolute signal. Westward movements when authorized to proceed must occupy track section immediately forward of Overlap Sign after which signal will clear if no conflicting route has been established.
6. **Whistle Signals for Hall Tower interlocking plant—**
Hastings main track..... One long.
Napier main track..... One long, one short, one long.
To Wye or inside track..... One long, two shorts, one long.

LINCOLN DIVISION

(Shubert - Lancaster)

NINTH SUBDIVISION

1. **Speed Restrictions—**
Zone—Between
Shubert and Nebraska City..... 10 MPH.
MP 6.73 and MP 6.82 between Nebraska City and Peru 5 MPH.
MP 18.40 and MP 18.80 between Peru and Brownville 5 MPH.
Nebraska City and Lancaster..... 25 MPH.
Over Missouri River bridge 4.76 Nebraska City..... 10 MPH.
Curve at MP 3.60..... 20 MPH.
Over Mo. Pac. crossing on roundhouse lead at Nebraska City 10 MPH.
Curve between MP 21.20 and MP 21.60..... 10 MPH.
Nebraska City and Payne..... 25 MPH.
Lincoln—
Over 27th Street, MP 58.50..... 10 MPH.
Westward trains, over 14th Street, MP 59.81..... 5 MPH.
Loaded tank cars 20 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
Between Shubert and Nebraska City..... 177,000 lbs.
Missouri River bridge MP 4.76..... 210,000 lbs.
Between Nebraska City and Lancaster
40 ft. or less in length..... 220,000 lbs.
Over 40 ft. long..... 263,000 lbs.
Between Shubert and Lancaster and between Nebraska City and Payne Bridge Derrick 975501 and 250 ton wrecking derrick must not operate.
3. **Train Register Exceptions—None.**
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Nebraska City—Operator on duty 7:00 A.M. to 5:00 P.M. daily except Saturday and Sunday. Trains must receive Clearance when operator on duty.
Shubert and Lancaster—Rule 83(B) does not apply.
5. **At Lancaster—**
Normal position of Jct. switch is for Eighth Subdivision.
6. Automatic Interlocking Nebraska City over Mo. Pac. Crossing Round House lead
7. Track between Nebraska City and Payne (5.7 miles) operated as one continuous yard.
8. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.
9. Payne Jct. switch at Nebraska City normal position for Payne.

LINCOLN DIVISION

(Ashland - Sioux City)

TENTH SUBDIVISION

1. **Speed Restrictions—**
Maximum Speed Permitted
Zone—Between
Ashland and Sioux City..... 49 MPH.
Curve MP 0.29 25 MPH.
Between Switches of Wye Ashland..... 10 MPH.
Westward trains approaching signal governing westward movement at MP 0.48..... 20 MPH.
At the approach signal of the following interlocking:
Eastward and Westward trains at U.P. crossing Yutan 30 MPH.
Eastward trains at U.P. crossing Fremont MP 29.98 20 MPH.
Eastward and Westward trains at C&NW crossing Nickerson 30 MPH.
Eastward trains at C&NW crossing Oakland..... 25 MPH.
Westward trains at C&NW crossing Dakota City.. 30 MPH.
Engines or leading car of trains between absolute signals at:
U.P. crossing at Yutan..... 20 MPH.
C&NW crossing east of Nickerson..... 20 MPH.
C&NW crossing at Oakland..... 20 MPH.
C&NW crossing at Dakota City..... 20 MPH.
Over Platte River Bridge 27.04..... 30 MPH.
MP 28.80 and MP 29.85, Fremont..... 10 MPH.
MP 27.70 and MP 28.80 and between MP 58.70 and MP 59.85. SD-24, U25C, U28C, U30C and U33C engines 40 MPH.
Between westbound absolute signal at CMStP&P crossing MP 223.35 (2nd Street) and 13th Street.. 10 MPH.
Ashland and Ferry: Bridge Derrick 975501 and 250 ton wrecking derrick..... 25 MPH.
Ferry and Sioux City: Bridge Derrick 975501 and 250 ton wrecking derrick must not operate, other derricks.. 20 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
40 ft. or less in length..... 220,000 lbs.
Over 40 ft. long..... 263,000 lbs.
Maximum gross weight of cars over Missouri River bridge between Ferry and Sioux City must not exceed 210,000 lbs. without authority of Superintendent.
SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks nor over Missouri River bridge at Sioux City.
Anderson Anderson Spur
Ferry Laketon scale track
South Sioux line track
Fremont when switching on Brewery track engine must not go beyond clearance point.
3. **Train Register Exceptions—**
Ashland—
Trains register by ticket.
Trains entering Third Subdivision through wye in eastward movement will not register.
Ferry—Trains will register when instructed to do so.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Fremont—Trains must receive Clearance.
5. **At Yutan**—When trains meet at Yutan, Westward trains holding main track will not pass approach signal until eastward trains are in clear of siding.
6. **At Fremont**—
Westward movements which have been delayed at U.P. or C&NW RR Crossing will notify operator of their intentions to move

through interlocking by depressing push button located in box east of track in vicinity of "L" Street.

Eastward trains setting out will stop to clear highway crossing, communicate with operator, and be governed by his instructions.

7. **At Sioux City—**

Interlocking of the Milwaukee Road and the BN direct connection is automatic with the exception that for BN through movements a push button at the BN 26th Street Yard Office should be used to extend the approach on that side in advance of cantilever signal 222.9.

Proceed indication will be received if the route to Ferry is clear and BN movements should not pass a more restrictive signal to avoid blocking Milwaukee and street crossings.

Instructions for operation are posted at the BN 26th Street Yard Office.

8. Automatic Interlocking not indicated at station:
C&NW Crossing 6.3 miles west of Fremont

LINCOLN DIVISION

(Ferry - O'Neill)

ELEVENTH SUBDIVISION

- Speed Restrictions—**

Zone—Between	Maximum Speed Permitted
	Freight
Ferry and Osmond	30 MPH.
Osmond and O'Neill	20 MPH.
Loaded tank cars:	
Between Ferry and Osmond.....	25 MPH.
Over bridge 27.83	10 MPH.
- Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

35 ft. or over in length.....220,000 lbs.

Between Ferry and O'Neill Bridge Derrick 975501 and 250 ton wrecking derrick must not operate.
- Train Register Exceptions—**

Ferry—Trains will register when instructed to do so.
- Clearance Provisions and Exceptions Rule 83(B)—**

Plainview and O'Neill—Rule 83(B) does not apply.
- Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Table Rock - Wymore)

TWELFTH SUBDIVISION

- Speed Restrictions—**

Zone—Between	Maximum Speed Permitted
	Freight
Table Rock and Wymore.....	35 MPH.
Curve on City track Pawnee.....	5 MPH.
At the approach signal of interlocking U.P. crossing MP 84.73	30 MPH.
Engine or leading car between absolute signals U.P. crossing MP 84.73	20 MPH.
Between Table Rock and Wymore Bridge Derrick 975501 and 250 ton wrecking derrick may operate 25 MPH. other derricks 30 MPH.	
- Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length.....220,000 lbs.

Over 40 ft. long.....263,000 lbs.

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

Wymore House track
No. 2 repair track
Belt track
City track

3. **Train Register Exceptions—**None.

4. **Clearance Provisions and Exceptions Rule 83(B)—**
Table Rock—

Operator on duty..... Monday—8:00 A.M. to 4:00 P.M.
Tuesday through Friday—continuous
Saturday 12:01 A.M. to 8:00 A.M. and
4:00 P.M. to 11:59 P.M.

Trains must receive Clearance when operator on duty.
Train order signal does not govern Twelfth Subdivision Trains.

- Lights on Train Order Signal will not be displayed.
- At Table Rock—**Normal position of Jct. Switch is for Eighth Subdivision.
- At Pawnee—**Air brakes must be coupled and working on cars handled on City track.
- Inside guard rail on center frog of UP Crossing, MP 84.73, east of Wymore, is one inch higher than the running rail. Trains handling snowplows, spreaders and similar equipment must see that equipment is raised sufficiently to clear this guard rail before passing over crossing.
- Wymore—**All tracks within yard limits are yard tracks.
- Automatic Interlocking not indicated at station:
UP Crossing 2.5 miles east of Wymore
- Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Pappio - Gilmore Jct.)

THIRTEENTH SUBDIVISION

- Speed Restrictions—**

Zone—Between	Maximum Speed Permitted
	Freight
Pappio and Gilmore Jct.....	30 MPH.
- Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length.....220,000 lbs.

Over 40 ft. long.....263,000 lbs.

Pappio and Gilmore Jct. Bridge Derrick 975501 and 250 ton wrecking derrick must not operate.
- Train Register Exceptions—**None.
- Clearance Provisions and Exceptions Rule 83(B)—**

Pappio and Gilmore Jct. Rule 83(B) does not apply.
- Trains and engines between Gilmore Jct. and South Omaha are governed by Union Pacific Bridge Subdivision Rules for employees of Tenant Lines.
- At South Omaha—**Four short and one long blast of whistle for UP switches.

LINCOLN DIVISION

(Brick Yard - Sargent)

FOURTEENTH SUBDIVISION

- Speed Restrictions—**

Zone—Between	Maximum Speed Permitted
	Freight
Brick Yard and Sargent.....	30 MPH.
Aurora and Brick Yard Bridge Derrick 975501, 250 ton wrecking derrick and other derricks may operate	20 MPH.
Over bridge 16.93 east of Central City.....	15 MPH.

At U.P. Interlocking Central City, engine or leading car, between Approach and absolute signal, and between absolute signals 20 MPH.

Loaded tank cars:

Between Aurora and Palmer..... 25 MPH.

Loaded tank car and Loaded Air Dump Cars:

Between MP 19.05 and 19.50, Central City..... 10 MPH.

Loaded tank cars between Palmer and Sargent..... 20 MPH.

MP 15.50 and MP 23.60, MP 28.75 and 30.10, MP 40.25 and Sargent:

Diesel engines GP-7 and GP-9..... 15 MPH.

Diesel engines SD-7 and SD-9..... 20 MPH.

2. Bridge, Engine and Heavy Car Restrictions—

Cars heavier than the following not permitted without authority of Superintendent:

Between Brick Yard and Palmer

40 ft. or less in length.....220,000 lbs.

Over 40 ft. long.....263,000 lbs.

Between Palmer and Sargent.

35 ft. or over in length.....220,000 lbs.

Between Aurora and Sargent Bridge Derrick 975501 and 250 ton wrecking derrick must not operate.

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

GiltnerElevator track

TrumbullElevator track

HastingsHouse track

HastingsBrick Yard

3. Train Register Exceptions—None

4. Clearance Provisions and Exceptions Rule 83(B)—

Brick Yard: Rule 83(B) does not apply, trains must receive clearance at Hastings Tower.

Aurora—Trains must receive clearance.

Palmer and Sargent—Rule 83(B) does not apply.

5. Lights on train order signals will not be displayed.

6. At Aurora—Train order signal does not govern Fourteenth Subdivision trains.

7. At Central City—

BN—U.P. crossing: BN train and engine movements approaching crossing, from either direction, must STOP at absolute signal. After stopping, trainman or engineer will proceed to crossing and operate the plant in accordance with instructions posted at the crossing.

8. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Palmer - Burwell)

FIFTEENTH SUBDIVISION

1. Speed Restrictions—

Zone—Between Maximum Speeds Permitted Freight

Palmer and Burwell..... 30 MPH.

Loaded tank cars 20 MPH.

Over bridge 40.68 west of Palmer..... 10 MPH.

2. Bridge, Engine and Heavy Car Restrictions—

Cars heavier than the following not permitted without authority of Superintendent:

Maximum gross weight of cars handled must not exceed 220,000 pounds.

Single Units only over Bridge 40.68, west of Palmer.

Palmer and Burwell Bridge Derrick 975501 and 250 ton wrecking derrick must not operate.

3. Train Register Exceptions—None.

4. Clearance Provisions and Exceptions Rule 83(B)—

Palmer and Burwell—Rule 83(B) does not apply.

5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(DeWitt - Hildreth)

SIXTEENTH SUBDIVISION

1. Speed Restrictions—

Zone—Between Maximum Speeds Permitted Freight

DeWitt and Edgar..... 25 MPH.

Edgar and Hildreth 35 MPH.

Tobias and Daykin..... 20 MPH.

Derricks Tobias to Daykin..... 10 MPH.

Edgar and Nelson 20 MPH.

GP7 and GP 9 engines between Edgar and Nelson..... 15 MPH.

Derricks Edgar and Nelson..... 10 MPH.

Loaded tank cars:

DeWitt and Edgar 20 MPH.

Edgar and Hildreth 25 MPH.

Engine or leading car at approach signal and between absolute signals of Interlocking Union Pacific crossing MP 57.26 20 MPH.

Over bridges 1.58, 65.84 and 98.30, GP-7, GP-9 and SD-7 engines (not exceeding two units) and SD-9 engines (Single Unit) 10 MPH.

2. Bridge, Engine and Heavy Car Restrictions—

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length.....220,000 lbs.

Over 40 ft. long.....263,000 lbs.

Maximum gross weight of cars handled between DeWitt and Swanton and between Edgar and Hildreth must not exceed 210,000 pounds.

Bridge derrick 975501 and 250 ton wrecking derrick must not operate.

3. Train Register Exceptions—

Strang—Train register at North switch West wye. Trains must register when instructed to do so.

4. Clearance Provisions and Exceptions Rule 83(B)—

DeWitt—Operator on duty 8:00 A.M. to 5:00 P.M. daily except Saturday and Sunday. Trains must receive Clearance when operator on duty.

Strang—Rule 83(B) does not apply.

5. Track between Edgar and Nelson also between Tobias and Daykin is considered industrial track, Rule 105 applies. Service between these points will be one engine movement only, which will not leave Edgar before 1:01 P.M. on Monday for Nelson, returning leave Nelson 1:40 P.M. On Thursday will not leave Edgar before 10:30 A.M. for Nelson, returning leave Nelson 11:10 A.M. Between Tobias and Daykin not leave Tobias before 9:01 A.M. on Tuesdays, Thursdays and Saturdays for Daykin, returning leave Daykin 9:30 A.M.

6. Lights on Train Order Signals will not be displayed.

7. At DeWitt—Train order signal does not govern Sixteenth Subdivision trains.

Normal position of Jct. Switch is for Sixth Subdivision.

8. At Strang—

Normal position of east and west wye switches of east wye on the Sixteenth Subdivision is for the Sixteenth Subdivision. Normal position of the South switch East wye is for the West leg of wye.

Normal position of east and west wye switches of west wye on the Sixteenth Subdivision is for the east and west legs of wye.

Normal position of the North switch West wye is for the West leg of wye.

9. Blue Hill—Normal position of junction switch (MP 86.83 and MP 87.02) is for the Nineteenth Subdivision.

10. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION
(Columbus Jct. - Columbus)

SEVENTEENTH SUBDIVISION

1. **Speed Restrictions—**

Zone—Between	Maximum Speeds Permitted
	Freight
Columbus Junction and MP 25.25 Seward.....	25 MPH.
MP 25.25 Seward and Columbus.....	30 MPH.
Loaded tank cars:	
Columbus Jct. and Seward.....	20 MPH.
Seward and Columbus	25 MPH.
Over bridge 5.81.....	20 MPH.
Over Highway Crossing MP 26.00 Seward.....	5 MPH.
Engine or leading car over main highway crossing just west of depot, Ulysses	5 MPH.
Over bridge 64.96	10 MPH.
Westward trains, MP 56.50 to MP 58.70.....	20 MPH.
Engine or leading car between absolute signals U.P. crossing, Columbus	20 MPH.
Engine or leading car over 21st Avenue Columbus.....	5 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length.....	220,000 lbs.
Over 40 ft. long.....	263,000 lbs.

Bridge Derrick 975501 and 250 ton Wrecking Derrick must not operate.

Maximum gross weight of cars handled between David City and Columbus must not exceed 220,000 pounds.
3. **Train Register Exceptions—None**
4. **Clearance Provisions and Exceptions Rule 83(B)—**

Columbus Jct.—Rule 83(B) does not apply.
5. **At Columbus—**

BN U.P. Crossing: BN train and engine movements approaching crossing from either direction, must STOP at absolute signal. After stopping, trainman or engineer will proceed to crossing and operate the plant in accordance with instructions posted at the crossing.

When setting cars to the Union Pacific transfer track, reverse movement must not be started to the transfer track until all cars in the cut are over the U.P. crossing.
6. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION
(Wymore - Red Cloud)

EIGHTEENTH SUBDIVISION

1. **Speed Restrictions—**

Zone—Between	Maximum Speeds Permitted
	Freight
Wymore and Red Cloud.....	35 MPH.
Engine or leading car between absolute signals U.P. crossing MP 114.86.....	20 MPH.
Engine or leading car between absolute signals C.R.I.&P. crossing MP 125.04.....	20 MPH.
Engine or leading car over Central Avenue and Bloom Street Superior	5 MPH.
Engine or leading car between absolute signals Missouri Pacific crossing MP 170.96.....	20 MPH.
Bridge Derrick 975501 and 250 ton wrecking derrick..	25 MPH.
Other derricks	30 MPH.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C	
Engines between Endicott and Red Cloud.....	30 MPH.

20

2. **Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length.....	220,000 lbs.
Over 40 ft. long.....	263,000 lbs.

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

Krider	House track
Odell	House track
Diller	Elevator track
Chester	House track
	Elevator track
Superior	Stock track
Bostwick	Elevator track
Red Cloud	Turkey track

Engines must not operate beyond frog of switch leading to Gyp track at Cement Plant, Superior.
3. **Train Register Exceptions—**

Trains will register at Odell Jct. and Lester Jct. when instructed to do so.
4. **Clearance Provisions and Exceptions Rule 83(B)—**

Odell Jct. and Lester Jct., Rule 83(B) does not apply.

Red Cloud—Operator on duty Tuesday through Saturday 7:30 A.M. to 4:30 P.M. Trains must receive Clearance when operator on duty.
5. Lights on train order signals will not be displayed.
6. **At Chester—**Trains or engines passing through Chester on any track other than main track must stop before crossing Thayer Avenue member of crew must flag trains or engines across entire width of street.
7. **At Superior—**Within the corporate limits, cars or engines must not be left standing less than 40 feet from street line and switching or light engine movements over Central Avenue and Bloom Streets must be protected by member of crew.

Missouri Pacific Crossing MP 170.96. Normal position of Gate is against MP trains. Rule 98(A) in effect.

8. **At Lester Jct.—**Normal position of junction switch is for Nineteenth Subdivision.
9. **Wymore—**All tracks within yard limits are yard tracks.
10. Automatic Interlocking not indicated at station:
CRI&P Crossing 8.9 miles west of Fairchild Spur.
11. Unless otherwise provided, protection against following trains as required by Rule 99 is not required, between Odell Jct. and Lester Jct.

LINCOLN DIVISION
(Hastings - Lester Jct.)

NINETEENTH SUBDIVISION

1. **Speed Restrictions—**

Zone—Between	Maximum Speeds Permitted
	Freight
Hastings and Lester Jct.....	30 MPH.
Engine or leading car of eastward trains over highway crossing at MP 1.04.....	5 MPH.
Engine or leading car over highway crossing MP 36.54	15 MPH.
Through turnout Lester Jct.....	10 MPH.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C..	25 MPH.
Bridge Derrick 975501 and 250 ton derricks may operate except must not exceed 10 MPH. over bridge 34.33.	
2. **Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length.....	220,000 lbs.
Over 40 ft. long.....	263,000 lbs.

21

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

CowlesHouse track
Blue HillElevator track
AyrCity track

3. **Train Register Exceptions—**

Ayr Jct.—Train register located at Jct. Switch No. 891 must register. Other trains will register when instructed to do so.

Lester Jct.—Trains will register when instructed to do so.

4. **Clearance Provisions and Exceptions Rule 83(B)—**

Lester Jct. and Ayr Jct.—Rule 83(B) does not apply.

5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required between Ayr Jct. and Lester Jct.

LINCOLN DIVISION

(Odell Jct. - Concordia)

TWENTIETH SUBDIVISION

1. **Speed Restrictions—** Maximum Speeds Permitted
Zone—Between Freight
Odell Jct. and Haddam..... 35 MPH.
Haddam and Concordia..... 30 MPH.
MP 1.40 and MP 1.65..... 10 MPH.
Bridge 16.08 10 MPH.
Bridges 21.88, 27.55, 39.15, 41.67, 42.99, 44.62, 48.30, 55.42, 64.69, 66.66..... 15 MPH.
At the approach signal of interlocking, Union Pacific crossing MP 14.60, Westward trains..... 15 MPH.
Engine or leading car between absolute signals Union Pacific Crossing MP 14.60..... 20 MPH.
Pile drivers 204617 and 204618 with empty flat car ahead of pile driver and empty flat car behind MS tank over bridges 1.61 and 16.08..... 10 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
35 ft. or over in length.....177,000 lbs.
Bridge Derrick 975501 and 250 ton wrecking derricks must not operate.
Single unit engines only may be operated.
3. **Train Register Exceptions—**
Odell Jct.—Trains will register when instructed to do so.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Odell Jct.—Rule 83(B) does not apply.
5. Lights on train order signals will not be displayed.
6. **At Concordia**—Trains or engines must stop before crossing Washington and Cedar Streets and member of crew must flag across entire width of street.
7. **At Odell Jct.** normal position junction switch is for the Eighteenth Subdivision.
8. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Bigelow - Skidmore)

TWENTY-FIRST SUBDIVISION

1. **Speed Restrictions—** Maximum Speeds Permitted
Zone—Between Freight
Bigelow and Skidmore..... 25 MPH.
MP 20 and Skidmore..... 20 MPH.
Engines over Bridges N-1.24 and 19.48..... 10 MPH.
Maitland MP 14.47 Elm Street..... 5 MPH.
Loaded tank cars and loaded air dump cars between Maitland and Skidmore..... 20 MPH.
Derricks 10 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Maximum gross weight of cars handled must not exceed 210,000 lbs. without authority of Superintendent.
Bridge derrick 975501 and 250 ton derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**None.
5. **Skidmore**—Derail on main track 50 feet west of depot crossing.
6. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Corning - Westboro)

TWENTY-SECOND SUBDIVISION

1. **Speed Restrictions—** Maximum Speeds Permitted
Zone—Between Freight
Corning and Westboro..... 25 MPH.
MP 1.90 and MP 3.04..... 10 MPH.
Engine heavier than 600 H.P. over Bridge 12.66..... 10 MPH.
Derricks 10 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Maximum gross weight of cars handled must not exceed 220,000 lbs. without authority of Superintendent.
Bridge derrick 975501 and 250 ton wrecking derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**None.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Ashland - Prague)

TWENTY-THIRD SUBDIVISION

1. **Speed Restrictions—** Maximum Speeds Permitted
Zone—Between Freight
Ashland and MP 3.00..... 25 MPH.
MP 3.00 and Prague..... 10 MPH.
Over Bridge 0.91..... 15 MPH.
Loaded tank cars and air dump cars between Ashland and MP 3.00..... 20 MPH.
Derricks 10 MPH.

2. **Bridge, Engine and Heavy Car Restrictions—**
Maximum gross weight of cars handled must not exceed 210,000 without authority of Superintendent.
Bridge derrick 975501 and 250 ton wrecking derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**None.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Tecumseh - Auburn)

TWENTY-FOURTH SUBDIVISION

1. **Speed Restrictions—**

	Maximum Speeds Permitted	
Zone—Between		Freight
Tecumseh and Auburn.....	25 MPH.	
Engine or leading car over highway crossing MP 43.81	10 MPH.	
Derricks	10 MPH.	
2. **Bridge, Engine and Heavy Car Restrictions—**
Maximum gross weight of cars handled must not exceed 220,000 lbs. without authority of Superintendent.
Bridge derrick 975501 and 250 ton wrecking derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**None.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Fairmont - Tobias)

TWENTY-FIFTH SUBDIVISION

1. **Speed Restrictions—**

	Maximum Speeds Permitted	
Zone—Between		Freight
Fairmont and Tobias.....	25 MPH.	
Loaded tank cars or loaded air dump cars.....	20 MPH.	
Derricks	10 MPH.	
2. **Bridge, Engine and Heavy Car Restrictions—**
Maximum gross weight of cars handled must not exceed 263,000 lbs. without authority of Superintendent.
Bridge derrick 975501 and 250 ton wrecking derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**None.
5. **Fairmont—**Normal position of junction switch east end is for Twenty-fifth subdivision.
6. Railroad crossing not protected by signals or gates not shown at station.
C&NW Crossing 4.7 miles west of Fairmont.
7. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Clay Center - Lushton)

TWENTY-SIXTH SUBDIVISION

1. **Speed Restrictions—**

	Maximum Speeds Permitted	
Zone—Between		Freight
Clay Center and Lushton.....	10 MPH.	
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent.
Between Clay Center and Sutton.....220,000 lbs.
Between Sutton and Lushton.....210,000 lbs.
Engines heavier than 600 H.P. cannot operate.
Bridge derrick 975501 and 250 ton wrecking derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**None.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Ayr Jct. - Huntley)

TWENTY-SEVENTH SUBDIVISION

1. **Speed Restrictions—**

	Maximum Speeds Permitted	
Zone—Between		Freight
Ayr Jct. and Huntley.....	10 MPH.	
2. **Bridge, Engine and Heavy Car Restrictions—**
Maximum gross weight of cars handled must not exceed 210,000 lbs. without authority of Superintendent.
Engines heavier than SD-7 cannot operate beyond 1000 feet west of Ayr Jct. switch.
Bridge derrick 975501 and 250 ton wrecking derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Ayr Jct. and Huntley—Rule 83(B) does not apply.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

LINCOLN DIVISION

(Kenesaw - Kearney)

TWENTY-EIGHTH SUBDIVISION

1. **Speed Restrictions—**

	Maximum Speeds Permitted	
Zone—Between		Freight
Kenesaw and Kearney.....	20 MPH.	
Derricks	10 MPH.	
GP-7 and GP-9 engines.....	15 MPH.	
Bridge 18.18	10 MPH.	
2. **Bridge, Engine and Heavy Car Restrictions—**
Maximum gross weight of cars handled must not exceed 263,000 lbs. without authority of Superintendent.
Bridge derrick 975501 and 250 ton wrecking derricks must not be operated.
3. **Train Register Exceptions—**None.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Kearney and Kenesaw—Rule 83(B) does not apply.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

ALLIANCE DIVISION

(Kenesaw - McCook)

FIRST SUBDIVISION

- | | | |
|---|---------------------------------|----------------|
| 1. Speed Restrictions— | Maximum Speeds Permitted | |
| Zone—Between | Passenger | Freight |
| MP 210 and MP 219.50 (Eastward)..... | | 55 MPH. |
| MP 219.50 and MP 230.50..... | 70 MPH. | 50 MPH. |
| Curve MP 229.50 | 65 MPH. | 50 MPH. |
| Head end of trains over Ogden Ave.
Oxford MP 233.80..... | 50 MPH. | 50 MPH. |
| MP 286.60 and MP 287.20..... | | 30 MPH. |
| MP 287.20 - MP 288.50 | 30 MPH. | 30 MPH. |
| SD-24, SD-45, U25C, U28C, SD-40,
U30C and U33C Engines on sidings at
Kenesaw, Axtell and Holdrege (south
side) | 25 MPH. | 25 MPH. |
- Trains must not exceed 25 MPH. through turnouts of controlled sidings.
- Engines on westward freight trains must not exceed 55 MPH. passing signal at MP 233.57.
- Engines on eastward freight trains must not exceed 55 MPH. passing signal at MP 250.50.
- 2. Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
- | | |
|-----------------------------------|--------------|
| 40 ft. or less in length..... | 220,000 lbs. |
| 40 ft. to 52.5 ft. in length..... | 263,000 lbs. |
| 52.5 ft. or longer..... | 315,000 lbs. |
- SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:
- | | |
|----------------|------------|
| Holdrege | Cob track |
| McCook | Mill track |
- 3. Train Register Exceptions—**
Oxford is a register station for all trains originating or terminating.
- 4. Clearance Provisions and Exceptions Rule 83(B)—**
Oxford—Operator on duty 7:30 A.M. to 4:30 P.M. daily except Saturday and Sunday. All trains to and from Fourth Subdivision must receive Clearance when operator on duty.
Kenesaw—Rule 83(B) does not apply.
- 5. Oxford**—Between 12 Noon and 1:00 P.M.; 3:45 P.M. and 4:30 P.M. Daily except Saturday and Sunday, freight trains stopping at Oxford must not block Ogden Street crossing.

ALLIANCE DIVISION

(McCook - Denver)

SECOND SUBDIVISION

- | | | |
|--|---------------------------------|----------------|
| 1. Speed Restrictions— | Maximum Speeds Permitted | |
| Zone—Between | Passenger | Freight |
| MP 287.81 to MP 288.50..... | 30 MPH. | 30 MPH. |
| MP 288.50 and MP 289.00 | 70 MPH. | 50 MPH. |
| MP 430.50 and MP 431.50 | 50 MPH. | 40 MPH. |
| MP 431.50 and MP 434.00 | 65 MPH. | 50 MPH. |
| Brush—Entering Sterling main tracks.. | 15 MPH. | 15 MPH. |
| Brush on Sterling main track over
Clayton Street Crossing..... | 10 MPH. | 10 MPH. |
| Eastward freight trains only
MP 449.00 to MP 434.00 | | 55 MPH. |
| MP 434.00 to MP 431.50..... | | 50 MPH. |
| MP 431.50 to MP 430.00..... | | 40 MPH. |
| Curve MP 506.40 | 70 MPH. | 50 MPH. |
| Head end or leading car over 72nd Ave.
crossing MP 535.32..... | 40 MPH. | 40 MPH. |
| MP 535.90 and MP 539.70..... | | 50 MPH. |
| Eastward freight trains only
MP 535.90 to MP 527.00..... | | 55 MPH. |
| Over U.P. Crossing MP 537.32..... | 60 MPH. | 30 MPH. |
| Head end or leading car over 56th Ave.
crossing MP 538.00 | 40 MPH. | 40 MPH. |
| MP 539.70 to signal MP 541.71..... | 30 MPH. | 30 MPH. |
| Signal MP 541.71 to 21st St. MP 541.85 | 15 MPH. | 15 MPH. |

SD-24, SD-45, U25C, U28C, SD-40,
U30C and U33C Engines on siding at
Wray

25 MPH. 25 MPH.

Ladora Yard Tracks: On tangent track
between gate and classification yard..

10 MPH.

Trains must not exceed 25 MPH. through turnouts of controlled sidings.

Engine on westward freight trains must not exceed 55 MPH. passing signal at MP 444.76.

Engine on eastward freight trains must not exceed 55 MPH. passing signal at MP 498.25.

2. Bridge, Engine and Heavy Car Restrictions—

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length

220,000 lbs.

40 ft. to 52.5 ft. in length.....

263,000 lbs.

52.5 ft. or longer.....

315,000 lbs.

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

Wray

Mill track

Brush

Rip track

Oil track

Moseley

Stock track

Fort Morgan

South spur track

Tampa Spur

Entire spur except 600 feet of tail track off wye

Tonville

Beet track

Barr

House track

3. Train Register Exceptions—

Akron—First class trains will not register at Akron.

Brush—Register station for all trains originating or terminating.

Denver—Trains originating or terminating at 38th Street Yard will register.

4. Clearance Provisions and Exceptions Rule 83(B)—

Akron—Unless otherwise provided, conductor or engineer, or both arriving at Akron, on all trains, must deliver all clearance forms, train orders, and messages to relieving conductor, or engineer, or both.

Brush—Rule 83(B) does not apply to trains off Eighth Subdivision enroute Second Subdivision.

- 5. Within CTC limits, trains finding a permissive indication displayed by a signal, which governs facing point movement over a spring switch, will comply with Rule 104(H) and in addition a member of the crew will contact control operator by telephone, located adjacent to the spring switch, when such communication is available.**

In CTC territory whenever trailing movement through spring switch is not authorized by signal indication, the spring switch must be operated by hand. When any switching movements are made over spring switch, Rule 276 will apply as to permission, time and working limits and notification to engineer.

- 6. At Brush**—Westward trains given permission to head in on No. 1 track will receive signal indication after east No. 1 track switch has been properly lined by hand.

- 7. At Ladora**—Member of crew will protect switching movements over Highway No. 2.

- 8. At Commerce City**—Trains using industry tracks must stop not more than 40 feet from 72nd Street crossing before moving over crossing.

- 9. At Denver**—All trains and engines at highways or street intersections with railroad tracks, where official traffic control devices are installed, must move into the intersection or highway only on clear (green light) traffic signal.

Trains or engines using Denver Union Terminal Railway Company's track must provide themselves with copy of and be governed by General and Interlocking rules of that Company.

ALLIANCE DIVISION

(Orleans Jct. - St. Francis)

THIRD SUBDIVISION

- | | | |
|--|---------------------------------|----------------|
| 1. Speed Restrictions— | Maximum Speeds Permitted | |
| Zone—Between | | Freight |
| Orleans Jct. and St. Francis..... | | 30 MPH. |
| Loaded tank cars | | 25 MPH. |
| All trains over highway crossing Atwood..... | | 5 MPH. |

SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks:

Long Island	House track
Almena	House track
Norton	BN trackage

SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C engines must not operate between Oronoque and Oberlin.

Between Flynn and Oberlin Bridge Derrick 975501 and 250 ton wrecking derricks must not operate.

Train Register Exceptions—None.

Clearance Provisions and Exceptions Rule 83(B)—
Flynn—Rule 83(B) does not apply.

Almena—CRI&P train orders and clearances will be delivered to westward BN trains.

Norton and Norcatur—CRI&P train orders and Clearances delivered to BN trains by BN operator.

BN Junction switches at Almena Jct., both switches of CRI&P siding, Norton and Oronoque, are equipped with electric switch locks controlled by CRI&P Operator at Norton. Telephones with instructions at same locations.

Norton. All trains will stop at highway crossing just west of city limits and flag movement over crossing.

Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

ALLIANCE DIVISION
(Holdrege - Sterling)
SIXTH SUBDIVISION

1. **Speed Restrictions** Maximum Speed Permitted
Zone—Between Freight
Holdrege and MP 24.00..... 25 MPH.
MP 24.00 and Sterling..... 30 MPH.
Haxtun, Engine or leading car over Washington Street
second crossing east of depot..... 10 MPH.
Sterling—Between approach signal and absolute signal
of Union Pacific interlocking crossing..... 15 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority
of Superintendent:
40 ft. or less in length.....220,000 lbs.
Over 40 ft. long.....263,000 lbs.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C engines
must not operate.
Between Holdrege and Sterling Bridge Derrick 975501 and 250
ton wrecking derricks must not operate.
3. **Train Register Exceptions—None.**
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Curtis—Unless otherwise provided, conductor or engineer or
both, arriving at Curtis on all trains must deliver clearance, train
orders and messages to relieving conductor, or engineer or both.
5. **Lights on train order signals will not be displayed.**
6. **Unless otherwise provided, protection against following trains as
required by Rule 99 is not required.**

ALLIANCE DIVISION
(Sterling - Carpenter)

SEVENTH SUBDIVISION

1. Speed Restrictions	Maximum Speed Permitted
Zone—Between	Freight
Sterling and Carpenter	20 MPH.
2. Bridge, Engine and Heavy Car Restrictions—	
Cars heavier than the following not permitted without authority of Superintendent:	
Over 35 ft. in length.....	177,000 lbs.

Between Sterling and Carpenter Bridge Derrick 975501, 250 ton derricks and rotary snow plow must not operate.
Engines heavier than 600 H.P. cannot operate.

3. **Train Register Exceptions**—None.
4. **Clearance Provisions and Exceptions Rule 83(B)**—None.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.

ALLIANCE DIVISION

(Sterling - Brush)

EIGHTH SUBDIVISION

1. **Speed Restrictions** Maximum Speed Permitted
Zone—Between Freight
Union and Brush..... 40 MPH.
Over Bridge 139.97..... 30 MPH.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C
also handling cars over 263,000 lbs. engines be-
tween Union and Brush..... 30 MPH.
2. **Bridge, Engine and Heavy Car Restrictions**—
Cars heavier than the following not permitted without authority
of Superintendent:
40 ft. or less in length.....220,000 lbs.
40 ft. to 52.5 ft. in length.....263,000 lbs.
52.5 ft. or longer.....315,000 lbs.
SD-24, SD-45, U25C, U28C, GP-40, SD-40 and U30C engines
must not operate on following tracks.
SterlingWelsh Elevator
Waycar track
Dago No. 1
Dago No. 2
3. **Train Register Exceptions**—None.
4. **Clearance Provisions and Exceptions Rule 83(B)**—
Sterling—In addition to BN Clearance, trains must receive UP
Clearance.
Brush—Trains for movement to Union Pacific Third Subdivision
must receive Union Pacific clearance.
5. **Union**—The movement of eastward trains is governed by Union
Pacific Signal to siding or main track and trains must stop before
passing signal and must not proceed until switches are properly
lined and signal indicates proceed.
Westward trains must stop clear of crossing to BN main track
and must not proceed until switches are properly lined.

ALLIANCE DIVISION

(Culbertson - Imperial)

NINTH SUBDIVISION

1. **Speed Restrictions** Maximum Speed Permitted
Zone—Between Freight
Culbertson and Imperial 25 MPH.
Engine or leading car over Arapahoe Street just west
of Depot Wauneta 10 MPH.
Enders over Highway No. 6 crossing M.P. 41.67..... 10 MPH.
Loaded tank cars..... 20 MPH.
2. **Bridge, Engine and Heavy Car Restrictions**—
Cars heavier than the following not permitted without authority
of Superintendent:
40 ft. or less in length.....220,000 lbs.
Over 40 ft. long.....263,000 lbs.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C engines
must not operate.
Between Culbertson and Imperial Bridge Derrick 975501 and
250 ton wrecking derrick must not operate.
3. **Train Register Exceptions**—None.

4. **Clearance Provisions and Exceptions Rule 83(B)**—
Culbertson—Rule 83(B) does not apply.
Imperial—Operator on duty 8:00 A.M. to 5:00 P.M. daily except
Saturday and Sunday. Trains must receive Clearance when oper-
ator on duty.
5. Lights on train order signals will not be displayed.
6. Unless otherwise provided, protection against following trains as
required by Rule 99 is not required.

ALLIANCE DIVISION

(Denver - Lyons)

TENTH SUBDIVISION

1. **Speed Restrictions** Maximum Speed Permitted
Zone—Between Freight
Broomfield and Longmont..... 25 MPH.
Longmont and Lyons 20 MPH.
Engine or leading car over crossings MP 18.12 and
MP 29.30..... 5 MPH.
Loaded tank cars..... 20 MPH.
Derricks 10 MPH.
2. **Bridge, Engine and Heavy Car Restrictions**—
Cars heavier than the following not permitted without authority
of Superintendent:
40 ft. or less in length..... 220,000 lbs.
40 ft. to 52.5 in length..... 263,000 lbs.
SD-24, SD-45, U-25C, U-28C, SD-40, U-30C and U-33C engines
must not operate.
Bridge derrick 975501 and 250 ton wrecking derricks must not
be operated.
3. **Train Register Exceptions**—
Broomfield—Trains will register when instructed to do so.
4. **Clearance Provisions and Exceptions Rule 83(B)**—
Longmont—Operator on duty as follows: 7:00 A.M. to 11:00
P.M. Monday through Friday, 7:00 A.M. to 3:00 P.M. Saturday
and Sunday. Trains must receive clearance when operator on
duty.
5. Unless otherwise provided, protection against following trains
as required by Rule 99 is not required.

ALLIANCE DIVISION

(Ravenna - Alliance)

ELEVENTH SUBDIVISION

1. **Speed Restrictions** Maximum Speeds Permitted
Zone—Between Freight
MP 127.74 and MP 127.95..... 20 MPH.
Head end westward freight trains at MP 175.10..... 55 MPH.
Head end of train over highway crossings from Fifth
street at stock yards, to Fourteenth street, first
crossing West of depot Broken Bow..... 30 MPH.
MP 364.54 and MP 365.25..... 25 MPH.
MP 365.25 and MP 365.50..... 20 MPH.
except not exceed 10 MPH. through turnouts.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C
engines on controlled sidings at Hazard, Ansley,
Merna, Anselmo, Linscott, Halsey, Thedford, Nor-
way, Mullen, Hecla, Whitman, Ashby, Bingham,
Antioch, Birdsell 25 MPH.
Through turnouts of controlled sidings in CTC limits.. 25 MPH.
2. **Bridge, Engine and Heavy Car Restrictions**—
Cars heavier than the following not permitted without authority
of Superintendent:
40 ft. or less in length.....220,000 lbs.
40 ft. to 52.5 ft. in length.....263,000 lbs.
52.5 ft. or longer.....315,000 lbs.
3. **Train Register Exceptions**—None.

4. **Clearance Provisions and Exceptions Rule 83(B)—Seneca**—Unless otherwise provided, conductor or engineer or both, arriving at Seneca on all trains must deliver all clearance forms, train orders and messages to relieving conductor or engineer, or both.
5. Within CTC limits, trains finding a permissive indication displayed by a signal, which governs facing point movement over a spring switch, will comply with Rule 104(H) and in addition a member of the crew will contact control operator by telephone, located adjacent to the spring switch, when such communication is available.
In CTC territory whenever trailing movement through spring switch is not authorized by signal indication, the spring switch must be operated by hand. When any switching movements are made over spring switch, Rule 276 will apply as to permission, time and working limits and notification to engineer.

ALLIANCE DIVISION

(Alliance - Edgemont)

TWELFTH SUBDIVISION

1. **Speed Restrictions**

Zone—Between	Maximum Speeds Permitted
Alliance and Edgemont	Freight 49 MPH.
MP 365.50 and MP 366.10	20 MPH.
except not exceed 10 MPH. through turnouts.	
MP 405.00 and MP 406.00	40 MPH.
MP 409.40 and MP 410.30	40 MPH.
MP 411.00 and MP 415.25	20 MPH.
MP 417.00 and MP 417.75	40 MPH.
Main track movement through turnout west end Crawford yard MP 423.10	25 MPH.
Trailing movement off siding Crawford through turnout at East end spring switch	15 MPH.
Derricks	25 MPH.
2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
40 ft. or less in length.....220,000 lbs.
40 ft. to 52.5 in length.....263,000 lbs.
Over 52.5 ft. or longer.....315,000 lbs.
3. **Train Register Exceptions—None.**
4. **Clearance Provisions and Exceptions Rule 83(B)—None.**
5. **Crawford**—C&NW trains have right to cross ahead of B.N. trains at crossing MP 423.12.
Inside guard rail on east end of track No. 23 (House Track) MP 422.92, is one and one-fourth inch higher than the running rail. Trains handling snow plows, spreaders and similar equipment must see that equipment is raised sufficiently to clear the guard rail before passing over it.
6. **Handling 80 ft. cars or longer.** (See All Subdivision Special Instructions, Item 4.) Alliance to Edgemont—MP 413 through MP 415.

ALLIANCE DIVISION

(Edgemont - Deadwood)

THIRTEENTH SUBDIVISION

1. **Speed Restrictions**

Zone—Between	Maximum Speed Permitted
Edgemont and Deadwood	25 MPH.
On 3 percent descending grade	15 MPH.
Over bridge 76.68	15 MPH.
Yates Spur MP 102.32 and Deadwood	15 MPH.
Loaded tank cars	20 MPH.

Minekahta and MP. 5.75.....	30 MPH.
MP 5.75 and Hot Springs.....	15 MPH.
Derricks Minnekahta and Hot Springs.....	10 MPH.
Kirk and Lead	15 MPH.

2. **Bridge, Engine and Heavy Car Restrictions—**
Cars heavier than the following not permitted without authority of Superintendent:
40 ft. or less in length.....220,000 lbs.
Over 40 ft. long.....263,000 lbs.
Between Hill City and Deadwood, Minnekahta and Hot Springs, also Kirk and Lead maximum gross weight of cars must not exceed 220,000 pounds.
Between Minnekahta and Hot Springs also Englewood and Deadwood Bridge derrick 975501 and 250 ton wrecking derrick must not operate.
Between Kirk and Lead derricks must not operate.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C engines may be operated with not more than two units coupled, at authorized speed restrictions between Edgemont and Custer also between Minnekahta and Hot Springs.
Diesel engines, except diesel switch engines, must not operate on following tracks:
Yates—from gate at east end of power plant trestle to end of track Orohondo.
Deadwood—Standard Oil Track, Slime Plant track, Pioneer Fruit Co. track from west end of platform at fruit house to east switch, Armour spur, Continental Oil track.
Only SW engine may operate between Kirk and Lead.
3. **Train Register Exceptions—**
Extra trains register at Minnekahta, Hill City and Kirk when instructed to do so.
No. 856 and 857 will register at Minnekahta and Hill City when instructed to do so.
4. **Clearance Provisions and Exceptions Rule 83(B)—**
Yard Engine will not make opposing movement against No. 856 and 857 between Kirk and Deadwood without train order authority. Deadwood yard engine must receive clearance.
5. Track between Minnekahta and Hot Springs also between Kirk and Lead is considered industrial track, Rule 105 applies. Line up received for 13th subdivision will cover.
6. **Hill City**—Between MP 60.40 and MP 60.71 and on both legs of the wye, also between Hill City and MP 4.36 on the 18th Subdivision, a third rail is installed for the operation of narrow gauge trains of the Black Hills Central Railroad Company. A narrow gauge spur track is located north of main track, connecting to east leg of wye at Hill City. A narrow gauge wye is located at MP 4.36 on the 18th Subdivision. Name of this station is Oblivion. All switches of the wye at Hill City are dual gauge. All switches whether standard, narrow or dual gauge must be lined and locked for normal position after each use.
7. Tunnels MP 72.35, 73.05, 76.98 and 85.32 will not clear man on top or side of car. Employees must not ride on top or side of car when moving through these tunnels.
8. Lights on train order signals will not be displayed.
9. Handling 80 foot or longer cars (See all subdivision special instructions Item 4.) Edgemont to Deadwood MP 5 through MP 107, Minnekahta to Hot Springs MP 5 through MP 12.90, Lead to Kirk MP 0.0 through MP 3.28.
10. Rotary plows must not operate between Minnekahta and Hot Springs.
Rotary snow plows 205098 and 205099 operate at reduced speed Kirk to Lead and observe close clearance MP 1.00 to Rock Cut.
11. Unless otherwise provided, protection against following trains as required by Rule 99 is not required between Edgemont and Kirk.
12. Yard limits between Deadwood and Kirk are operated as one continuous yard.

ALLIANCE DIVISION

(Alliance - Guernsey)

FOURTEENTH SUBDIVISION

- Speed Restrictions**

Zone—Between	Maximum Speed	Permitted Freight
Alliance-Guernsey		49 MPH.
Alliance and MP 0.78 and through hand operated crossover from Guernsey main track to Edgemont main track	20 MPH.	
except not exceeding 10 MPH. through all turnouts.		
MP 1.00; Engine or leading car over highway crossing	30 MPH.	
Scottsbluff: Engine or leading car over Broadway crossing	10 MPH.	
On Scottsbluff Spur	15 MPH.	
Northport: Through main track turnout North Wye switch	15 MPH.	
West wye switch Northport: Through main track turnout West Wye switch	15 MPH.	
Guernsey: Main track movement through turnout west end of yard, MP 95.80	15 MPH.	
- Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length	220,000 lbs.
Over 40 ft. long	263,000 lbs.
except between Alliance and Northport	
52.5 ft. or longer	315,000 lbs.

Bayard-Mitchell—Cars must not be moved beyond engine limit sign on sugar track serving Great Western Sugar Company.
SD-24, SD-45, U25C, U28C, GP-40, SD-40, U30C and U33C engines must not operate on following tracks.
Bayard Factory Yard Pulp track
Scottsbluff Factory Yard.....Seed track beyond switch to No. 9 track
Factory No. 1 track
Rock and Syrup track
Factory No. 6 track
- Train Register Exceptions—**

Northport and West Wye Switch Northport—Trains will register when instructed to do so.
- Clearance Provisions and Exceptions Rule 83(B)**—None.

ALLIANCE DIVISION

(Guernsey - Casper)

FIFTEENTH SUBDIVISION

- Speed Restrictions**

Zone—Between	Maximum Speed	Permitted Freight
Guernsey-Casper		49 MPH.
Guernsey and MP 115.00	40 MPH.	
MP 195.00 and Casper	40 MPH.	
Tunnels between Guernsey and Wendover	25 MPH.	
Curves between MP 107.30 and MP 109.60	25 MPH.	
MP 112.37 and MP 112.53	15 MPH.	
MP 114.00 and MP 115.00	35 MPH.	
MP 126.40 and MP 127.50	35 MPH.	
Westward freight trains between MP 196.80 and MP 197.00	25 MPH.	
Between Guernsey and Casper Bridge Derrick 975501 and 250 ton wrecking derrick	25 MPH.	
- Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length	220,000 lbs.
Over 40 ft. long	263,000 lbs.
- Train Register Exceptions—**

Wendover—Trains will register when instructed to do so.
- Clearance Provisions and Exceptions Rule 83(B)**—None.

- Centralized Traffic Control in effect between MP 95.75 and MP 102.25.
- Dave**—Following Pacific Power tracks must not be used without authority of Chief Dispatcher: Track No. 1 beyond 1000 feet South of No. 1 track switch. Track No. 2 and Track No. 3 beyond switch to the South leg of Wye. The South leg of Wye.
- Casper**—Yard engines or leading car, must stop before crossing West Yellowstone Highway.
Cars must not be left on track serving Black Hills Bentonite Company, MP 203.70, between main track switch and derail located 529 feet West of main track clearance point.

ALLIANCE DIVISION

(Northport - Sterling)

SIXTEENTH SUBDIVISION

- Speed Restrictions**

Zone—Between	Maximum Speed	Permitted Freight
Northport and Sterling	45 MPH.	
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C	40 MPH.	

Northport:
Engine or leading car of train between absolute signals at UP crossing..... 20 MPH.
Eastward freight trains at approach signal to interlocking UP crossing..... 25 MPH.

Bridgeport:
Lyman Richey Sand track..... 10 MPH.

Bridgeport:
Through main track turnouts west of depot and at east end of yard..... 15 MPH.
Between Sterling and Ackerman handling cars exceeding 263,000 pounds 30 MPH.
- Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length	220,000 lbs.
40 ft. to 52.5 in length	263,000 lbs.
52.5 ft. or longer	315,000 lbs.

Not more than one SD-24, SD-45, U25C, SD-40, U30C or U33C engine, may be operated on Lyman Richey sand track.
- Train Register Exceptions—**

Northport and Bridgeport—Trains will register when instructed to do so.
- Clearance Provisions and Exceptions Rule 83(B)**—

Northport—Rule 83(B) does not apply.
Bridgeport—Operator on duty 7:00 A.M. to 4:00 P.M. daily except Sunday. Trains must receive Clearance when operator on duty.

ALLIANCE DIVISION

(Casper - Bonneville)

SEVENTEENTH SUBDIVISION

- Speed Restrictions**

Zone—Between	Maximum Speed	Permitted Freight
Casper and Bonneville		49 MPH.
SD-24, SD-45, U25C, U28C, SD-40, U30C and U33C engines: Between Bucknum and Bonneville	40 MPH.	
Head end of eastward trains MP 204.85	25 MPH.	
Between Casper and Bonneville Derrick 975501 and 250 ton wrecking derrick must not exceed 25 MPH.		
- Bridge, Engine and Heavy Car Restrictions—**

Cars heavier than the following not permitted without authority of Superintendent:

40 ft. or less in length	220,000 lbs.
Over 40 ft. long	263,000 lbs.
- Train Register Exceptions—**

Illco and Shobon—Trains will register when instructed to do so.
- Clearance Provisions and Exceptions Rule 83(B)**—

Casper—Trains enroute Rocky Mountain Division must receive such clearance at Casper.
Bonneville—Operator on duty 8:00 A.M. to 5:00 P.M. daily except Saturday and Sunday. Trains must receive clearance when operator on duty.

Unless otherwise provided, all trains arriving at Bonneville must deliver all clearance, train orders and messages to relieving conductor or engineer, or both.

5. **At Casper**—Yard engines or leading car, must stop before crossing West Yellowstone Highway. Cars must not be left on track serving Black Hills Bentonite Company, MP 203.70, between main track switch and derail located 529 feet west of main track clearance point.
6. **At Ilco**—The Junction switch of BN R.R. and C&NW Ry. is equipped with controlled electric switch lock and signals. C&NW trains in both directions must stop clear of absolute signals and be governed by instructions posted in box.

ALLIANCE DIVISION

(Hill City - Keystone)

EIGHTEENTH SUBDIVISION

1. **Speed Restrictions**—Maximum Speed Permitted
 Zone—Between
 Hill City and Keystone..... 15 MPH.
 Derricks 10 MPH.
2. **Bridge, Engine and Heavy Car Restrictions**—
 Cars heavier than the following not permitted without authority of Superintendent:
 40 ft or less in length..... 220,000 lbs.
 Over 40 ft. long..... 263,000 lbs.
 Bridge Derrick 975501 and 250 ton wrecking derrick must not operate.
3. **Train Register Exceptions**—None.
4. **Clearance Provisions and Exceptions Rule 83(B)**—None.
5. Unless otherwise provided, protection against following trains as required by Rule 99 is not required.
6. **Handling 80 foot or longer cars**—
 (See all subdivision special instructions Item 4.)
 Hill City to Keystone MP 0.00 through MP 9.45.

SPEED TABLE

Time Per Mile			Miles	Time Per Mile			Miles
Min.	Sec.	Per Hour		Min.	Sec.	Per Hour	
	46		78.3	1	18		46.2
	47		76.6	1	20		45.0
	48		75.0	1	22		43.9
	49		73.5	1	24		42.9
	50		72.0	1	26		41.9
	51		70.6	1	28		40.9
	52		69.2	1	30		40.0
	53		67.9	1	33		38.7
	54		66.7	1	36		37.5
	55		65.5	1	39		36.4
	56		64.3	1	42		35.3
	57		63.2	1	45		34.3
	58		62.1	1	50		32.7
	59		61.0	1	55		31.3
1	0		60.0	2	—		30.0
1	1		59.0	2	10		27.7
1	2		58.1	2	20		25.7
1	3		57.1	2	30		24.0
1	4		56.3	2	40		22.5
1	5		55.4	3	—		20.0
1	6		54.5	3	30		17.1
1	7		53.7	4	—		15.0
1	8		52.9	5	—		12.0
1	9		52.2	6	—		10.0
1	10		51.4	7	—		8.6
1	12		50.0	8	—		7.5
1	14		48.6	9	—		6.7
1	16		47.4	10	—		6.0